Material Safety Data Sheet

acc. to OSHA and ANSI

<u> </u>	dentification of substance:
•	Product details:
•	Trade name: Graphene Nanoplatelets/NMP Paste
•	Manufacturer/Supplier:
	Nanostructured & Amorphous Materials, Inc. 16840 Clay Road, Suite #113 Houston, TX 77084, USA
C	omposition/Data on components:
₽	Chemical characterization: Description: (CAS#) Graphene Nanoplatelets, 5 wt%
	Dispersant, 1 wt% N-methyl-2-pyrolidone (CAS # 872-50-4), 94 wt%
	Eye Contact: May cause eye irritation Skin Contact: May cause sensitization by prolonged skin contact.
•	Inhalation: Potentially toxic for humans if inhaled of NMP steam.
•	Ingestion: Lower oral acute toxicity, but may irritate gastrointestinal tract
F	irst aid measures
•	Skin contact: Rinse with water and soap
•	Eye contact: Rinse with water. Obtain medical attention if pain, blinking or redness persists
Ð	Ingestion: Rinse mouth with water. Don't be treatment for vomiting. Seek immediate medical advice.

```
Flash Point: 91 °C (196 °F) - closed cup (NMP)
  Explosion Limits: Unknown
   Fire extinguishing: Powder, carbon-rich gas, foam fire-extinguisher, drying
    sand, Water (spray)
6 Accidental release measures
 • After release:
    Adequate ventilation should be provided in the storage area.
    Wear Safety glasses, impervious gloves, gas mask while working.
    Keep away from sources of ignition.
 • Measures for environmental protection:
    Do not allow material to be released to the environment without proper
    governmental permits.
 • Measures for cleaning/collecting: Ensure adequate ventilation.
 Additional information:
    See Section 7 for information on safe handling
    See Section 8 for information on personal protection equipment.
    See Section 13 for disposal information.
7 Handling and storage
 • Handling:
    Provide good ventilation and an exhaust system in the work area. In case of
    insufficient ventilation, wear suitable respiratory equipment
 • Information for safe handling:
   Keep container tightly sealed.
    Store in cool, dry place in tightly closed containers.
    Ensure good ventilation at the workplace.
 Information about protection against explosions and fires:
   Keep away from sources of ignition.
 Storage:
 Requirements to be met by storerooms and receptacles:
   No special requirements.

    Information about storage in one common storage facility:

    Store away from oxidizing agents.
    Store away from halogens.
    Do not store together with acids.
  Further information about storage conditions:
    Keep container tightly sealed.
    Store in cool, dry conditions in well sealed containers.
8 Exposure controls and personal protection
```

• Additional information about design of technical systems:

Properly operating chemical fume hood designed for hazardous chemicals and having an average face velocity of at least 100 feet per minute.

Components with limit values that require monitoring at the workplace:

Graphite

oraphree	2
	mg/m ³
ACGIH TLV	2
Belgium TWA	2.5
Finland TWA	5
France VME	2
Germany MAK	6
Ireland TWA	5
Korea TLV	2
Netherlands MAC-TGG	2
Poland TWA	2
Sweden NGV	5 (dust)
Switzerland MAK-W	2.5
United Kingdom	5-LTEL
USA PEL	15 mppcf
Netherlands MAC-TGG Poland TWA Sweden NGV Switzerland MAK-W United Kingdom	2 2 5 (dust) 2.5 5-LTEL

- Additional information: No data
- Personal protective equipment

• General protective and hygienic measures

The usual precautionary measures for handling chemicals should be followed. Keep away from foodstuffs, beverages and feed. Remove all soiled and contaminated clothing immediately. Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin.

- Breathing equipment:
 Use suitable respirator when high concentrations are present.
- Protection of hands: Impervious gloves
- Eye protection: Safety glasses
- Body protection: Protective work clothing.

9 Physical and chemical properties:

General Information

- Form: Paste
- **Odor:** Odorless

- Value/Range Unit Method
- Change in condition

-24 °C (-11 °F) (subl/vac) Melting point/Melting range: Boiling point/Boiling range: 202 °C (396 °F) • Sublimation temperature / start: Not determined 91 °C (196 °F) - closed cup Flash point: Ignition temperature: 270 °C (518 °F) Decomposition temperature: Not determined • Danger of explosion: Product can present an explosion hazard. Explosion limits: Lower: 1.3 % (V) Upper: 9.5 % (V) • Vapor pressure: 0.39 - 0.43 hPa (0.29 - 0.32 mmHg) at 20 °C (68 °F) 1.32 hPa (0.99 mmHg) at 40 °C (104 °F) Density: 1-1.10 g/mL at 25 °C (77 °F) Solubility in / Miscibility with • Water: Not Determined 10 Stability and reactivity Thermal decomposition / conditions to be avoided: Unstable, avoid Sunlight, heat, open flame, high-temperature, spark, static, or other ignition source • Materials to be avoided: Contact with strong oxidizing agents, strong acid, reducing agents, bases. Dangerous reactions No dangerous reactions known if store under recommended conditions • Dangerous products of decomposition: Carbon monoxide and carbon dioxide 11 Toxicological information Acute toxicity CNT: Primary irritant effect: on the skin: Irritant to skin and mucous membranes. on the eye: Irritating effect. Sensitization: No sensitizing effects known.

•	
	Acute toxicity NMP:
	ORL-RAT LD50 3914 mg kg-1 ORL-MUS LD50 7725 mg kg-1
	IPR-RAT LD50 2266 mg kg-1
	SKN-RBT LD50 8000 mg kg-1
	Irritating to eyes.
	Irritating to respiratory system. Irritating to skin.
•	Sub-acute to chronic toxicity:
	The inhalation of graphite, both natural and synthetic, has caused pneumoconiosis in exposed workers. The pneumoconiosis found is similar to coal worker's pneumoconiosis.
•	Additional toxicological information:
	To the best of our knowledge the acute and chronic toxicity of carbon nanotubes is not fully known.
	No classification data on carcinogenic properties of this material is available from the EPA, IARC, NTP, OSHA or ACGIH.
12 <u>I</u>	Ecological information:
•	General notes:
	Do not allow material to be released to the environment without proper governmental permits.
13 1	Disposal considerations
10 1	
•	Product:
•	Recommendation
-	Consult state, local or national regulations to ensure proper disposal.
	consult state, focal of national regulations to ensult proper alsposal.
•	Unclean packaging:
•	
•	Unclean packaging:
• • 14 <u>1</u>	Unclean packaging: Recommendation:
• • 14 <u>1</u>	Unclean packaging: Recommendation: Disposal must be made according to official regulations.
Us	Unclean packaging: Recommendation: Disposal must be made according to official regulations.
Us	Unclean packaging: Recommendation: Disposal must be made according to official regulations. Transport information se precaution during transport in order to prevent accidental spill. Store in a bol place avoiding direct sunlight when transportation. DOT regulations:
Us	<pre>Unclean packaging: Recommendation: Disposal must be made according to official regulations. Fransport information se precaution during transport in order to prevent accidental spill. Store in a bol place avoiding direct sunlight when transportation. DOT regulations: NA-Number: 1993 Class: CBL Packing group: III</pre>
Us	Unclean packaging: Recommendation: Disposal must be made according to official regulations. Transport information se precaution during transport in order to prevent accidental spill. Store in a bol place avoiding direct sunlight when transportation. DOT regulations:
Us	<pre>Unclean packaging: Recommendation: Disposal must be made according to official regulations. Transport information See precaution during transport in order to prevent accidental spill. Store in a bool place avoiding direct sunlight when transportation. DOT regulations: NA-Number: 1993 Class: CBL Packing group: III Proper shipping name: Combustible liquid (N-methyl-2-pyrolidone) Reportable Quantity (RQ): Marine pollutant: No</pre>
Us	<pre>Unclean packaging: Recommendation: Disposal must be made according to official regulations. Transport information See precaution during transport in order to prevent accidental spill. Store in a bool place avoiding direct sunlight when transportation. DOT regulations: NA-Number: 1993 Class: CBL Packing group: III Proper shipping name: Combustible liquid (N-methyl-2-pyrolidone) Reportable Quantity (RQ):</pre>
Us	<pre>Unclean packaging: Recommendation: Disposal must be made according to official regulations. Transport information See precaution during transport in order to prevent accidental spill. Store in a bool place avoiding direct sunlight when transportation. DOT regulations: NA-Number: 1993 Class: CBL Packing group: III Proper shipping name: Combustible liquid (N-methyl-2-pyrolidone) Reportable Quantity (RQ): Marine pollutant: No</pre>

 Land transport ADR/RI 	ID (cross-border)			
• ADR/RID class:	None			
• Maritime transport IMDG:				
• IMDG Class:	None			
• Air transport ICAO-TI	• Air transport ICAO-TI and IATA-DGR:			
• ICAO/IATA Class:	None			
 Transport/Additional information: Not dangerous according to the above specifications. 				
15 Regulations				
 Product related hazard informations: 				
• Hazard symbols: Xi Irritant, Combustible Liquid, Target Organ Effect, Teratogen				
• Risk phrases: Irritating to eyes and respiratory system.				
• Safety phrases:				
In case of contact wi medical advice.	ith eyes, rinse immediately with plenty of water and seek			
• National regulations	• National regulations			
	All components of this product are listed in the U.S. Environmental Protection Agency Toxic Substances Control Act Chemical Substance Inventory.			
 Information about lin For use only by techr 	nitation of use: nically qualified individuals.			
16 Other information				
16 Other information:				
gathered by them, and sh information to ensure pr This information is furr conformance with this Ma	is information only as a supplement to other information hould make independent judgement of suitability of this coper use and protect the health and safety of employees. hished without warranty, and any use of the product not in aterial Safety Data Sheet, or in combination with any other the responsibility of the user.			
- ·	_			